

April 7, 2016

Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

# Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## SEAMER GEAR OIL

### SEAMER OIL-150P

**Seamer Oil-150P** is specially formulated to lubricate the gear systems found in “once through” designed can closers used in food canning operations. This machine design allows the oil to cascade through the gears, lubricating as it goes, until it is discharged into the sanitary drain system from the bottom of the machine. **Seamer Oil-150P** is blended using the highest quality base stocks and utilizes an additive package that provides excellent wear, EP, and corrosion properties. This superior formulation passes all 12 stages of the FZG Gear Test. Tested extensively, **Seamer Oil-150P** has demonstrated exceptional results when used in this application.

Manufactured in Summit's ISO 21469 Certified facility, this product is produced under the strictest hygienic guidelines for food grade lubricant production. **Seamer Oil-150P** is NSF H1 approved for use where there is a possibility of incidental contact with the food being processed.

### Physical Properties

PRODUCT	150P
ISO Grade	150
Viscosity	
@ 40°C, cSt	146
@ 100°C, cSt	14.5
Viscosity Index	97
Flash Point, °F (°C)	445 (229)
Fire Point, °F (°C)	485 (252)
Pour Point, °F (°C)	0 (-18)
FZG Gear Test	12+ Pass
NSF Registration	H1
Kosher Approved	Yes
Halal Certified	Yes

**Shelf Life:** Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.